



CATALOGUE



ADEL

ADAM

ADAM

ADAM

ADAM

ADAM

ADAM

ADAM

ADAM

ADAM

ADAM

The Collection

Our unique range of doors combines style, elegance and sustainability. The first all-'GREEN' interior door with zero formaldehyde emissions and 100% waterproof features in Cyprus!

- 5 layers of paint for durability and aesthetics
- Waterproof door and frame
- Soundproofing up to 29 decibels
- Zero formaldehyde emissions
- Magnetic lock
- Invisible hinges for a sleek look
- Handle included



217



218





The 1 i adore!

ANAEL

1 PANEL DOOR

OVEN PAINTED "Matt Lacquered Veneer" 5 LAYERS PAINT

NOISE REDUCTION 29 DECIBELS

4.5 CM DOOR



ACOUSTIC DOOR



WATERPROOF



GREEN DOOR



3 CONCEALED HINGES



The 1 i adore!

ADEL

2 PANEL DOOR
OVEN PAINTED "Matt Lacquered Veneer"
5 LAYERS PAINT
NOISE REDUCTION 29 DECIBELS
4.5 CM DOOR



ACOUSTIC DOOR



WATERPROOF



GREEN DOOR



3 CONCEALED HINGES





The 1 i adore!

MEI

4 LINE L DESIGN DOOR
OVEN PAINTED "Matt Lacquered
Veneer" 5 LAYERS PAINT
NOISE REDUCTION 29 DECIBELS
4.5 CM DOOR



ACOUSTIC DOOR



WATERPROOF



GREEN DOOR



3 CONCEALED HINGES



The 1 i adore!

EMMA

2 PANEL DOOR
OVEN PAINTED "Matt Lacquered
Veneer" 5 LAYERS PAINT
NOISE REDUCTION 29 DECIBELS
4.5 CM DOOR



ACOUSTIC DOOR



WATER PROOF



GREEN DOOR



3 CONCEALED HINGES





The 1 i adore!

ZOG

PURE STYLE DESIGN DOOR
OVEN PAINTED "Matt Lacquered
Veneer" 5 LAYERS PAINT
NOISE REDUCTION 29 DECIBELS
4.5 CM DOOR



ACOUSTIC DOOR



WATERPROOF



GREEN DOOR



3 CONCEALED HINGES



The 1 i adore!

ZOHAR

6 LINE DOOR

OVEN PAINTED "Matt Lacquered
Veneer" 5 LAYERS PAINT

NOISE REDUCTION 29 DECIBELS

4.5 CM DOOR



ACOUSTIC DOOR



WATERPROOF



GREEN DOOR



3 CONCEALED HINGES





The 1 i adore!

SLIDE

PURE TYPE DESIGN DOOR
OVEN PAINTED "Matt Lacquered
Veneer" 5 LAYERS PAINT
4.5 CM DOOR



ACOUSTIC DOOR



WATERPROOF



GREEN DOOR



On-Site Construction Openings



Opening Width:

The construction opening width options are 80cm and 90cm.


Opening Height:

The height of the opening is measured from the ground to the top of the construction opening. The recommended height is 220 cm.



Wall Thickness:

The wall thickness ranges from 10 cm to 17 cm. Any thickness exceeding 17 cm will incur an additional charge for a crossbar with a 4 cm increment.



Electrical Points:

Electrical points must be positioned at least 15 cm away from the door opening.





The 1 i adore!

Agia Varvara Industrial Area, Paphos

Tel: +357 99 750 095 / 26 322 327 Email: onedoorcyprus@gmail.com

WWW.ONE-DOOR.EU

