

The Collection

An innovative and modern design that has never been seen before. A smooth matte finish, clean and unique door that will impress all. Our customers are very attached t o the term "modern". In our initial meeting with a new customer, one common request is to plan and design innovative, modern doors. They desire a home that is both beautiful and

unique without compromising on quality.



GET IN TOUCH

- ♀ AGIA BARBARA INDUSTRIAL AREA PAPHOS
- WWW.ONE-DOOR.EU
- +357-99750095
- R LIMOR5558@WALLA.COM













ADEL

2 PANEL DOOR OVEN PAINTED "Matt Lacquered Veneer" **5 LAYERS PAINT** NOISE REDUCTION 29 DECIBELS 4.5 CM DOOR



GREEN DOOR



M

WATERPROOF




AYELET

PURE STYLE DOOR OVEN PAINTED "Matt Lacquered Veneer" 5 LAYERS PAINT NOISE REDUCTION 29 DECIBELS 4.5 CM DOOR











ZOHAR

6 LINE DOOR OVEN PAINTED "Matt Lacquered Veneer" 5 LAYERS PAINT NOISE REDUCTION 29 DECIBELS 4.5 CM DOOR



GREEN DOOR



WATERPROOF







MEI

4 LINE L DESIGN DOOR OVEN PAINTED "Matt Lacquered Veneer" 5 LAYERS PAINT NOISE REDUCTION 29 DECIBELS 4.5 CM DOOR



GREEN DOOR







EMMA

2 PANEL DOOR OVEN PAINTED "Matt Lacquered Veneer" 5 LAYERS PAINT NOISE REDUCTION 29 DECIBELS 4.5 CM DOOR









WATER PROOF







ANAEL

1 PANEL DOOR OVEN PAINTED "Matt Lacquered Veneer" 5 LAYERS PAINT NOISE REDUCTION 29 DECIBELS 4.5 CM DOOR









SLIDE

PURE TYPE DESIGN DOOR OVEN PAINTED "Matt Lacquered Veneer" 5 LAYERS PAINT 4.5 CM DOOR







GREEN DOOR





ZOG


PURE STYLE DESIGN DOOR OVEN PAINTED "Matt Lacquered Veneer" 5 LAYERS PAINT NOISE REDUCTION 29 DECIBELS 4.5 CM DOOR





Sec. 14







On-Site Construction Openings

Opening Width:

The construction opening width options are 80cm and 90cm.

Opening Height:

The height of the opening is measured from the ground to the top of the construction opening. The recommended height is 220 cm.

Wall Thickness:


The wall thickness ranges from 10 cm to 17 cm. Any thickness exceeding 17 cm will incur an additional charge for a crossbar with a 4 cm increment.

Electrical Points:

Electrical points must be positioned at least 15 cm away from the door opening.









Door Handles & Accessories











Trusted Partners



Lifetime Warranty



Customer Service

ONE-DOOR.EU